

Product No. **8351-400-10**
 S No.
 EAN No. **7312908351409**



Ohm 140/115

A family of porcelain luminaires for walls, ceilings and tables. Designed by Kauppi & Kauppi, the soft curves and restrained silhouette references to both Scandinavian design and ancient Japanese tableware.

Specification

| | |
|------------------|--------------------------|
| Base material | Porcelain |
| Lampholder | GX53 |
| Light source | GX53, Max 7W (not incl.) |
| Voltage | 230V |
| Installation | Ceiling/wall |
| Base colour | White NCS S 1502-G50Y |
| Safety class | I |
| Protection class | IP44 |
| Energy class | - |
| T _a | -30 - +25 |
| Height | 112 mm |
| Diameter Ø | 138 mm |
| Glass | Matt opal |
| Thread | 123,5 mm |
| Weight | 1,067 kg |
| Design | Kauppi & Kauppi |

Installation

Insert the mains supply cable through the bottom inlet. Fix the light fitting to the wall or to the ceiling with suitable screws. Connect the leads to the terminal block. Fasten the LED module and then tighten the shade by turning it clockwise. Make sure the gasket between the glass and base is in place.

Technical information

Silicone gasket between glass and base. Two Ø 5mm holes for installation. Two holes CC measurement 70 mm, alternatively two hidden holes CC measurement 60-66 mm. One bottom inlet for two mains supply cable. Terminal block for connection of 3 x 2,5 mm². Bridging is possible. Bottom inlet. No knock out openings.

Maintenance

Switch off the power to the fixture. Remove the shade and clean it. Do not use cleaning agents containing solvents. Change the LED module if necessary. Check the gasket and change it if necessary. Replace the shade.

Spare parts

Shade: 1-6167-30
 Gasket: 02789

If the luminaire is modified the person responsible for the modification shall be considered manufacturer. Subject to errors in text. We reserve the right to change the technical specifications (without notice).

