according to Regulation (EC) No. 1907/2006 (REACH)



1.0.0

Trade name: Jaeger Badewannen- / Fliesenlack

Stammlack - alle Farben - 887 / 897

Revision date: 04.07.2016 Version: Print date: 16.07.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Jaeger Badewannen- / Fliesenlack Stammlack - alle Farben - 887 / 897 (8870000)

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses

Coating product to be used by professional / private user. For further information please refer to the technical data

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Paul Jaeger GmbH & Co KG **Street:** Siemensstr. 6

Postal code/city: 71696 Möglingen

Telephone: 07141 / 2444-0 **Telefax:** 07141 / 2444-44

Information contact: info@jaegerlacke.de

1.4 Emergency telephone number

Vergiftungs-Informations-Zentrale Freiburg Tel. 0761/19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Eye Irrit. 2; H319 - Serious eye damage/eye irritation: Category 2A; Causes serious eye irritation. Skin Sens. 1; H317 - Skin sensitisation: Category 1; May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Exclamation mark (GHS07)

Signal word

Warning

Hazard components for labelling

CYCLOHEXANOL, 4,4-(1-METHYLETHYLIDENE)BIS-, POLYMER WITH (CHLOROMETHYL)OXIRANE; CAS No.: 30583-72-3 3-AMINOPROPYLTRIETHOXYSILANE; CAS No.: 919-30-2

Hazard statements

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

Precautionary statements

Keep out of reach of children. P102 P103 Read label before use.

Avoid breathing dust/fume/gas/mist/vapours/spray. P261

Wash hands thoroughly after handling. P264

Page: 1/8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Jaeger Badewannen- / Fliesenlack

Stammlack - alle Farben - 887 / 897

Revision date: 04.07.2016 Version: 1.0.0

Print date: 16.07.2018

> P272 Contaminated work clothing should not be allowed out of the workplace.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P321 Specific treatment (see note on this label). P501 Dispose of contents/container to disposal

Special rules for supplemental label elements for certain mixtures

FUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

None

SECTION 3: Composition / information on ingredients

3.2 Mixtures

Hazardous ingredients

CYCLOHEXANOL, 4,4-(1-METHYLETHYLIDENE)BIS-, POLYMER WITH (CHLOROMETHYL)OXIRANE; CAS No.: 30583-72-3

Weight fraction: 2,5 - 10 %

Classification 1272/2008 [CLP]: Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Irrit. 2; H319

METHANOL; EC No.: 200-659-6; CAS No.: 67-56-1 Weight fraction: < 0.5 %

Classification 1272/2008 [CLP]: Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H311 Acute Tox. 3; H331

STOT SE 1: H370

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Page: 2/8

according to Regulation (EC) No. 1907/2006 (REACH)



1.0.0

Version:

Jaeger Badewannen- / Fliesenlack Trade name:

Stammlack - alle Farben - 887 / 897

Revision date: 04.07.2016 Print date: 16.07.2018

Suitable extinguishing media

alcohol resistant foam Carbon dioxide (CO2) Water mist Extinguishing powder

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

Burning produces heavy smoke. Do not inhale explosion and combustion gases. Use suitable breathing apparatus.

Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NOx) Carbon monoxide. Carbon dioxide (CO2) Hydrocarbons

5.3 Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Wear breathing apparatus if exposed to vapours/dusts/aerosols. See protective measures under point 7 and 8.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

Clear spills immediately.

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

For cleaning up

Clean with detergents. Avoid solvent cleaners.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Measures to prevent fire

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Use only antistatically equipped (sparkfree) tools. Provide earthing of containers, equipment, pumps and ventilation facilities. Wear anti-static footwear and clothing Electrical equipment should be protected to the appropriate standard.

Environmental precautions

Shafts and sewers must be protected from entry of the product.

Specific requirements or handling rules

All work processes must always be designed so that the following is excluded: Inhalation of vapours or spray/mists Inhalation of dust/particles Skin contact Eye contact Never use pressure to empty container. Wear personal protection equipment (refer to section 8).

Additional information

Keep/Store only in original container. Comply with the health and safety at work laws. Do not allow to enter into surface water or drains.

7.2 Conditions for safe storage, including any incompatibilities

To follow: Betriebssicherheitsverordnung (BetrSichV)

Hints on joint storage

Page: 3 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Jaeger Badewannen- / Fliesenlack

Stammlack - alle Farben - 887 / 897

Revision date: 04.07.2016 Version: 1.0.0

Print date: 16.07.2018

Materials to avoid

Strong acid Strong alkali Oxidising agent

Further information on storage conditions

See information supplied by the manufacturer. Keep/Store only in original container. Store in a place accessible by authorized persons only. Keep container tightly closed. Always close containers tightly after the removal of product.

Storage temperature: of °C up to °C

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

METHANOL; CAS No.: 67-56-1

Limit value type (country of origin): TWA (EC)

200 ppm / 260 mg/m³ Limit value:

Remark: Н Version: 07.02.2006

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Personal protection equipment

Eye/face protection

Suitable eye protection

Eye glasses with side protection

Skin protection

Hand protection

Suitable material: Butyl caoutchouc (butyl rubber)

Required properties: liquid-tight.

Breakthrough time (maximum wearing time): > 480 min See information supplied by the manufacturer.

Thickness of the glove material: 0,7mm

Recommended glove articles: When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

Additional hand protection measures: Check leak tightness/impermeability prior to use. Do not wear gloves near rotary machines and tools. Take recovery periods for skin regeneration. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Remark: For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Body protection

Required properties: antistatic.

Recommended material: Natural fibres (e.g. cotton) heat-resistant synthetic fibres

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values

Suitable respiratory protection apparatus

Filtering device (full mask or mouthpiece) with filter: A

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

Page: 4/8

according to Regulation (EC) No. 1907/2006 (REACH)



1.0.0

Version:

Trade name: Jaeger Badewannen- / Fliesenlack

Stammlack - alle Farben - 887 / 897

Revision date: 04.07.2016 Print date: 16.07.2018

9.1 Information on basic physical and chemical properties

Appearance

Physical state: liquid Colour: please refer to label

Odour characteristic

Safety relevant basis data

Initial boiling point and boiling (1013 hPa) 35 °C range: Flash point : 100 °C Density: (20°C) g/cm³ ca. 1,5

Flow time: (20 °C) DIN-cup 4 mm

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

Stable under recommended storage and handling conditions(See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapours. Exothermal decomposition with formation of: Carbon dioxide. Carbon monoxide. Nitrogen oxides (NOx). carbon black.

SECTION 11: Toxicological information

There are no data available on the preparation/mixture itself. Classification according to Regulation (EC) No. 1272/2008 [CLP] See Sections 2 and 3 for details.

11.1 Information on toxicological effects

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from shortterm and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Acute effects

Acute toxicity No information available.

Irritant and corrosive effects

Skin corrosion/irritation Serious eye damage/eye irritation No information available.

Page: 5 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



1.0.0

Version:

Trade name: Jaeger Badewannen- / Fliesenlack

Stammlack - alle Farben - 887 / 897

Revision date: 04.07.2016

Print date: 16.07.2018

Sensitisation

Respiratory or skin sensitisation No information available.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

No information available.

Germ cell mutagenicity

No information available.

Reproductive toxicity

No information available.

STOT-single exposure

No information available.

STOT-repeated exposure

No information available.

Aspiration hazard

No information available.

SECTION 12: Ecological information

There are no data available on the preparation/mixture itself. Do not allow to enter into surface water or drains.

12.1 Toxicity

No information available.

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Do not allow to enter into surface water or drains. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

08 01 12 Waste paint and varnish other than those mentioned in 08 01 11

Other disposal recommendations

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information contact your local waste authority. Using information provided in this safety data sheet, advice should be obtained from the local waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Page: 6 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



1.0.0

Version:

Trade name: Jaeger Badewannen- / Fliesenlack

Stammlack - alle Farben - 887 / 897

Revision date: 04.07.2016

Print date: 16.07.2018

SECTION 14: Transport information

14.1 UN number

No dangerous goods in sense of this transport regulation.

14.2 UN proper shipping name

No dangerous goods in sense of this transport regulation.

14.3 Transport hazard class(es)

No dangerous goods in sense of this transport regulation.

14.4 Packing group

No dangerous goods in sense of this transport regulation.

14.5 Environmental hazards

No dangerous goods in sense of this transport regulation.

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Other regulations (EU)

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC-value: ca. 20 g/l

15.2 Chemical Safety Assessment

No information available.

SECTION 16: Other information

16.1 Indication of changes

16.2 Abbreviations and acronyms

16.3 Key literature references and sources for data

16.4 Relevant H- and EUH-phrases (Number and full text)

H225 Highly flammable liquid and vapour.

H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H370 Causes damage to organs.

16.5 Training advice

None

16.6 Additional information

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for

Page: 7 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Jaeger Badewannen- / Fliesenlack Stammlack - alle Farben - 887 / 897

Revision date : 04.07.2016 **Version :** 1.0.0

Print date : 16.07.2018

ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Page: 8 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Jaeger Badewannen- / Fliesenlack Härter

alle Gebindegrößen

Revision date : 04.07.2016 **Version :** 1.0.0

Print date : 16.07.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Jaeger Badewannen- / Fliesenlack Härter alle Gebindegrößen (889000H)

3-AMINOPROPYLTRIETHOXYSILANE; REACH registration No.: 01-2119480479-24; CAS No.: 919-30-2; EC No.: 213-

048-4; INDEX No.: 612-108-00-0

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses

Coating product to be used by professional / private user. For further information please refer to the technical data sheet

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Paul Jaeger GmbH & Co KG **Street:** Siemensstr. 6

Postal code/city: 71696 Möglingen

Telephone: 07141 / 2444-0 **Telefax:** 07141 / 2444-44

Information contact: info@jaegerlacke.de

1.4 Emergency telephone number

Vergiftungs-Informations-Zentrale Freiburg Tel. 0761/19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute Tox. 4; H302 - Acute toxicity (oral): Category 4; Harmful if swallowed.

Eye Dam. 1 ; H318 - Serious eye damage/eye irritation : Category 1 ; Causes serious eye damage.

Skin Corr. 1B; H314 - Skin corrosion/irritation: Category 1B; Causes severe skin burns and eye damage.

Skin Sens. 1; H317 - Skin sensitisation: Category 1; May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms





Corrosion (GHS05) · Exclamation mark (GHS07)

Signal word

Danger

Hazard statements

H318 Causes serious eye damage. H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

Precautionary statements

P102 Keep out of reach of children.

Page: 1 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Jaeger Badewannen- / Fliesenlack Härter

alle Gebindegrößen

Revision date: 04.07.2016 **Version:** 1.0.0

Print date : 16.07.2018

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P270 Do no eat, drink or smoke when using this product.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see note on this label).

P330 Rinse mouth.

P501 Dispose of contents/container to disposal

2.3 Other hazards

None

SECTION 3: Composition / information on ingredients

3.1 Substances

Substance name: 3-AMINOPROPYLTRIETHOXYSILANE

INDEX No.: 612-108-00-0

EC No.: 213-048-4

REACH No.: 01-2119480479-24

CAS No.: 919-30-2 **Purity:** 100 % [mass]

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. If unconscious place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam Carbon dioxide (CO2) Water mist Extinguishing powder

Page: 2/8

according to Regulation (EC) No. 1907/2006 (REACH)



1.0.0

Trade name : Jaeger Badewannen- / Fliesenlack Härter

alle Gebindegrößen

Revision date: 04.07.2016 Version:

Print date : 16.07.2018

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

Burning produces heavy smoke. Do not inhale explosion and combustion gases. Use suitable breathing apparatus.

Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NOx) Carbon monoxide. Carbon dioxide (CO2) Hydrocarbons

5.3 Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Wear breathing apparatus if exposed to vapours/dusts/aerosols. See protective measures under point 7 and 8.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

Clear spills immediately.

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

For cleaning up

Clean with detergents. Avoid solvent cleaners.

6.4 Reference to other sections

None

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Measures to prevent fire

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Use only antistatically equipped (sparkfree) tools. Provide earthing of containers, equipment, pumps and ventilation facilities. Wear anti-static footwear and clothing Electrical equipment should be protected to the appropriate standard.

Environmental precautions

Shafts and sewers must be protected from entry of the product.

Specific requirements or handling rules

All work processes must always be designed so that the following is excluded: Inhalation of vapours or spray/mists Inhalation of dust/particles Skin contact Eye contact Never use pressure to empty container. Wear personal protection equipment (refer to section 8).

Additional information

Keep/Store only in original container. Comply with the health and safety at work laws. Do not allow to enter into surface water or drains.

7.2 Conditions for safe storage, including any incompatibilities

To follow: Betriebssicherheitsverordnung (BetrSichV)

Hints on joint storage

Materials to avoid

Strong acid Strong alkali Oxidising agent

Page: 3 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Jaeger Badewannen- / Fliesenlack Härter

alle Gebindegrößen

Revision date : 04.07.2016 **Version :** 1.0.0

Print date : 16.07.2018

Further information on storage conditions

See information supplied by the manufacturer. Keep/Store only in original container. Store in a place accessible by authorized persons only. Keep container tightly closed. Always close containers tightly after the removal of product.

Storage temperature: of °C up to °C

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

None

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Personal protection equipment

Eye/face protection

Suitable eye protection

Eye glasses with side protection

Skin protection

Hand protection

Suitable material: Butyl caoutchouc (butyl rubber)

Required properties: liquid-tight.

Breakthrough time (maximum wearing time): > 480 min See information supplied by the manufacturer.

Thickness of the glove material : 0.5 mm

Recommended glove articles: When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

Additional hand protection measures: Check leak tightness/impermeability prior to use. Do not wear gloves near rotary machines and tools. Take recovery periods for skin regeneration. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Remark: For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Body protection

Required properties: antistatic.

Recommended material: Natural fibres (e.g. cotton) heat-resistant synthetic fibres

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values

Suitable respiratory protection apparatus

Filtering device (full mask or mouthpiece) with filter: A

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state: liquid
Colour: please refer to label

Odour

Page: 4/8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Jaeger Badewannen- / Fliesenlack Härter

alle Gebindegrößen

Revision date : 04.07.2016 **Version :** 1.0.0

Print date : 16.07.2018

characteristic

Safety relevant basis data

Initial boiling point and boiling range : (1013 hPa) > 35 °C Flash point : > 100 °C Density : (20 °C) ca. 0,9 g/cm^3

Flow time : (20 °C) 60 s DIN-cup 4 mm

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

Stable under recommended storage and handling conditions(See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapours. Exothermal decomposition with formation of: Carbon dioxide. Carbon monoxide. Nitrogen oxides (NOx). carbon black.

SECTION 11: Toxicological information

There are no data available on the preparation/mixture itself. Classification according to Regulation (EC) No. 1272/2008 [CLP] See Sections 2 and 3 for details.

11.1 Information on toxicological effects

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Acute effects

Acute toxicity No information available.

Irritant and corrosive effects

Skin corrosion/irritation Serious eye damage/eye irritation No information available.

Sensitisation

Respiratory or skin sensitisation No information available.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

No information available.

Germ cell mutagenicity

No information available.

Page: 5 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Jaeger Badewannen- / Fliesenlack Härter

alle Gebindegrößen

Revision date : 04.07.2016 **Version :** 1.0.0

Print date : 16.07.2018

Reproductive toxicity

No information available.

STOT-single exposure

No information available.

STOT-repeated exposure

No information available.

Aspiration hazard

No information available.

SECTION 12: Ecological information

There are no data available on the preparation/mixture itself. Do not allow to enter into surface water or drains.

12.1 Toxicity

No information available.

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

None

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Do not allow to enter into surface water or drains. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

08 01 12 Waste paint and varnish other than those mentioned in 08 01 11

Other disposal recommendations

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information contact your local waste authority. Using information provided in this safety data sheet, advice should be obtained from the local waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

SECTION 14: Transport information

14.1 UN number

UN 3267

14.2 UN proper shipping name

Land transport (ADR/RID)

CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (3-AMINOPROPYLTRIETHOXYSILANE)

Page: 6 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Jaeger Badewannen- / Fliesenlack Härter

alle Gebindegrößen

Revision date: 04.07.2016 **Version:** 1.0.0

Print date : 16.07.2018

Sea transport (IMDG)

CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (3-AMINOPROPYLTRIETHOXYSILANE)

Air transport (ICAO-TI / IATA-DGR)

CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (3-AMINOPROPYLTRIETHOXYSILANE)

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es): 8
Classification code: C7
Hazard identification number (Kemler
No.): 80
Tunnel restriction code: E
Special provisions: LQ22 · E 2
Hazard label(s): 8

Sea transport (IMDG)

Class(es): 8
Special provisions: LQ 1 | E 2
Hazard label(s): 8
Air transport (ICAO-TI / IATA-DGR)

Class(es): 8
Special provisions: E 2

14.4 Packing group

Η

14.5 Environmental hazards

Land transport (ADR/RID): No Sea transport (IMDG): No

Air transport (ICAO-TI / IATA-DGR): No

14.6 Special precautions for user

Transport within the user's premises: Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Other regulations (EU)

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC-value: ca. 20 g/l

15.2 Chemical Safety Assessment

No information available.

SECTION 16: Other information

16.1 Indication of changes

None

16.2 Abbreviations and acronyms

None

16.3 Key literature references and sources for data

None

16.4 Relevant H- and EUH-phrases (Number and full text)

Page: 7 / 8

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Jaeger Badewannen- / Fliesenlack Härter

alle Gebindegrößen

Revision date : 04.07.2016 **Version :** 1.0.0

Print date : 16.07.2018

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

16.5 Training advice

None

16.6 Additional information

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Page: 8 / 8